



**WALL MOUNTING
SOCKET DN9c**



Wall box metal 20°
593B2M25



Socket-outlet
1914081



PLUG DN9c



Straight handle poly
513POD30



Inlet
1918081

MAIN FEATURES

Rated current/contact (wiring according to standard)	30 A	Ambient temperature	-40 °C to +60 °C
Σ of currents (contacts)	≤ 210 A	Flexible wiring (min-max)	1-6 mm²
Maximum voltage	415 V	Stranded wiring (min-max)	1,5-10 mm²
IP protection lid closed	IP55	Wiring (terminals)	screw-type
IP protection plug connected	IP54	Keying positions	2
Shock resistance	IK09		



In case of Different
voltage, think of
MARECHAL® keying
position coding

**SOCKET-
OUTLET female
DN9c (30 A)**



**INLET male
DN9c (30 A)**



50 V AC	6P	1914060	1918060
50 V AC	7P	1914070	1918070
50 V AC	8P	1914080	1918080
50 V AC	9P	1914090	1918090
415 V AC	5P+E	1914051	1918051
415 V AC	6P+E	1914061	1918061
415 V AC	7P+E	1914071	1918071
415 V AC	8P+E	1914081	1918081

► The contacts can be assigned either power or signal.

