

XREEL® 250

Cable reel made of special plastics Ø250mm

Stable carrying rack with ergonomic handle made of extremely durable plastic, central brake mechanism as well as 2 parking positions for the plug.

Equipment:

- 4 x safety sockets with child protection (shutter) 16A 250V
- Thermal protection, power indicator light and safety plug (rubber) with dual earthing system



Cable length	Cable type	Cable colour	IP	Cat.No.
25m	H05RR-F 3G1,5 rubber sheated cable	■ black	IP20	9250005-p
25m	H05VV-F 3G1,5 PVC sheated cable	■ black	IP20	9250002-p

Equipment:

- 4 x safety sockets with child protection (shutter), sealing bulge and self closing hinged lid 16A 250V
- Thermal protection, power indicator light and safety plug (rubber) with dual earthing system



Cable length	Cable type	Cable colour	IP	Cat.No.
25m	H05RR-F 3G1,5 rubber sheated cable	■ black	IP54	9250006-p
25m	H05RR-F 3G1,5 rubber sheated cable	■ black	IP54	9250007-p*
33m	H05RR-F 3G1,5 rubber sheated cable	■ black	IP54	9250024-p
25m	H05VV-F 3G1,5 PVC sheated cable	■ black	IP54	9250004-p
33m	H05VV-F 3G1,5 PVC sheated cable	■ black	IP54	9250023-p
25m	H07RN-F 3G1,5 rubber sheated cable	■ black	IP54	9250013-p
25m	H07RN-F 3G2,5 rubber sheated cable	■ black	IP54	9250029-p
25m	H07RN-F 3G2,5 rubber sheated cable	■ black	IP54	9250025-p*
25m	N07V3V3-F 3G1,5 PVC building site cable	■ yellow	IP54	9250156-p
25m	N07V3V3-F 3G2,5 PVC building site cable	■ yellow	IP54	9250016-p

¹⁾ Cable type can only be used in Austria on building sites. (National regulations have to be observed!)

1)

Empty cable reel made of special plastics Ø250mm

Stable carrying rack with ergonomic handle made of extremely durable plastic, central brake mechanism as well as 2 parking positions for the plug.

Empty reel with crank, cable entry and strain relief



Description	Cat.No.
Empty reel (without central panel), colour: black	9250998-p
Blind cover (undrilled, unequipped), colour: black	925001
Central panel 4xSSD 4x safety socket IP54 incl. thermal protection and operation display, ready wired on main terminal	925004
Central panel 3xSSD 3x safety socket IP54 individually replaceable incl. thermal protection, ready wired on main terminal	925006

XREEL® 250



Cable reel made of special plastics Ø250mm

Stable carrying rack with ergonomic handle made of extremely durable plastic, central brake mechanism as well as 2 parking positions for the plug.

Equipment:

- 3 x safety sockets (individually replaceable), with sealing bulge and self-closing hinged lids 16A 250V
- Thermal circuit breaker, solid rubber plug (dual earthing system)

Cable length	Cable type	Cable colour	IP	Cat.No.
25m	H07RN-F 3G1,5 rubber sheathed cable	■ black	IP54	9250012-p
33m	H07RN-F 3G1,5 rubber sheathed cable	■ black	IP54	9250022-p
25m	H07RN-F 3G2,5 rubber sheathed cable	■ black	IP54	9250034-p
25m	H07BQ-F 3G1,5 polyurethane cable	■ orange	IP54	9250010-p
30m	H07BQ-F 3G1,5 polyurethane cable	■ orange	IP54	9250033-p
33m	H07BQ-F 3G1,5 polyurethane cable	■ orange	IP54	9250026-p
25m	H07BQ-F 3G2,5 polyurethane cable	■ orange	IP54	9250018-p
25m	N07V3V3-F 3G1,5 PVC building site cable	■ yellow	IP54	9250121-p
25m	N07V3V3-F 3G1,5 PVC building site cable	■ yellow	IP54	9250001-p*
33m	N07V3V3-F 3G1,5 PVC building site cable	■ yellow	IP54	9250019-p
20m	N07V3V3-F 3G2,5 PVC building site cable	■ yellow	IP54	9250020-p
25m	N07V3V3-F 3G2,5 PVC building site cable	■ yellow	IP54	9250021-p

¹⁾ Cable type can only be used in Austria on building sites. (National regulations have to be observed!)

1)



Equipment:

- 2 x CEE-sockets 16A 3p 4h 110V
- Thermal circuit breaker and CEE plug 16A 3p 4h 110V

Cable length	Cable type	Cable colour	IP	Cat.No.
25m	H07RN-F 3G2,5 rubber sheathed cable	■ black	IP54	9250008-p

Equipment:

- 3 x sockets 13A 250V british system IP54
- Thermal circuit breaker and plug 13A 2p+PE british system IP32

Cable length	Cable type	Cable colour	IP	Cat.No.
25m	H07RN-F 3G1,5 rubber sheathed cable	■ black	IP32	9250009-p

Equipment:

- 1 x CEE-socket 16A 3p 6h 230V
- 1 x safety socket with sealing bulge and self-closing hinged lid 16A 250V
- Thermal circuit breaker and CEE plug 16A 3p 6h 230V

Cable length	Cable type	Cable colour	IP	Cat.No.
20m	H07RN-F 3G2,5 rubber sheathed cable	■ black	IP54	9250035-p

Equipment samples: (other versions on request)

*French/Belgian system with child protection (shutter)

Recommended max. cable lengths [m] XREEL® 250 / 310

XREEL® 250 / 310	H05VV-F	H05RR-F	H07RN-F	N07V3V3-F	H07BQ-F
3G1,5	33 / 60	33 / 60	33 / 60	33 / 60	33 / 60
3G2,5	25 / 50	25 / 50	25 / 50	25 / 50	25 / 50
5G2,5	- / -	- / 33	- / 33	- / 33	- / 33

For general information about cable types see page 333!